

# FR Lunawood Spruce Powderhorn

## Product Specifications



### Description

**FR Lunawood Spruce** is fire-retardant-treated wood (FRTW) siding for exterior applications.

Lunawood ThermoWood® is thermally modified with heat and steam. ThermoWood® offers enhanced dimensional stability and durability for harsh climates.

Wood Source FR products are pressure treated with Thermex-FR by Chemco to meet Class A flame spread per the 30-minute ASTM E84 / UL 723 test (ASTM E2768). Certifications provided separately.



**Finish:** Powderhorn

### Specifications

|                    |                    |
|--------------------|--------------------|
| Manufacturer       | Wood Source        |
| Material           | FR Lunawood Spruce |
| Species            | Nordic Spruce      |
| Finish             | Powderhorn         |
| Grade              | Knotty A-Grade     |
| Certification      | PEFC               |
| FRTW Treatment     | Thermex-FR         |
| Treatment Facility | Chemco, Inc.       |
| Flame Spread       | Class A            |
| Moisture Content   | 5-8%               |

### Profiles

1x6 Luna Sharp HF (Smooth T&G)

- Weight: 1.86 lbs / SF
- Actual thickness:  $\frac{3}{4}$  inch
- Exposed face: 4  $\frac{7}{8}$  inches
- Reveal size:  $\frac{1}{16}$  inch

1x6 Luna Layer (Brushed Shiplap)

- Weight: 1.68 lbs / SF
- Actual thickness:  $\frac{3}{4}$  inch
- Exposed face: 5  $\frac{1}{4}$  inches
- Reveal size:  $\frac{1}{8}$  inch

1x8 Luna Layer (Brushed Shiplap)

- Weight: 1.58 lbs / SF
- Actual thickness:  $\frac{3}{4}$  inch
- Exposed face: 7  $\frac{1}{8}$  inches
- Reveal size:  $\frac{1}{8}$  inch

Lengths: 6 feet - 20 feet